

SoftwareUCM Unified Communication & Collaboration Software Solution

SoftwareUCM is a software-based PBX solution that provides a scalable business communication and collaboration platform with powerful features and integrations that enable teams to be more productive than ever before. This software PBX unifies all business communications onto one centralized platform that provides voice and video calling, meetings, chat, data, analytics, mobility, facility access, intercoms, video surveillance, and more. SoftwareUCM supports all SIP endpoints and the Wave app for desktop, mobile, and web, allowing teams to communicate and collaborate from anywhere on nearly any device. By providing a state-of-the-art suite of communication and collaboration features, bank-grade security, advanced customization, and a variety of scalable plan options, SoftwareUCM is the ideal PBX solution for enterprises, small-to-medium sized businesses, retail, hospitality, and residential deployments.



Comprehensive unified communication and collaboration features



GDMS provides seamless cloud setup, management, monitoring, and provisioning



Zero configuration provisioning of Grandstream SIP endpoints



Supports up to 5000 users and up to 1000 concurrent calls



Pair with UCM RemoteConnect NAT firewall traversal service to ensure secure remote connections



Supports Full-Band Opus voice codec, H.265/H.264/ H.263/H.263+/VP8 video codec, jitter resilience up to 50% packet loss



Built-in audio, video, chat, and web meeting platform; supports desktop, mobile devices, and SIP endpoints



Instant messaging/chat, screen sharing, whiteboard, file sharing, recording, meeting assistant, & more



API and SDK available for thirdparty integrations, including CRM and PMS platforms



Wave app for mobile, desktop, and web allows communication from anywhere on any device



Supports Customer Service platforms, WhatsApp, Telegram, etc. Built-in live chat for desktop & mobile



Integrate with CRM, PMS, Microsoft Teams, Office 365, Google Drive and more





Enterprise-Grade Communications

SoftwareUCM unifies all business communications onto one centralized platform. This software-based PBX provides businesses and resellers with complete control of their UC solution, as it is hosted on their local physical machines, virtual machines, or cloud platforms.



Enterprise-Grade Security Protection

SoftwareUCM provides end-toend data encryption, storage, and backup mechanisms. It is equipped with state-of-the-art anti-malware protection to ensure the security of all data. When multiple customers are being managed, SoftwareUCM ensures data isolation and security between software instances.



Deployment Flexibility and Mullti-Tenant

SoftwareUCM can be deployed on virtual machines, physical machines, or cloud platforms. Thanks to multi-tenant support, resellers can install and maintain multiple customers through a single installation, allocating resources flexibly to various independent software instances.



Powerful Integrations and Expansions

Easily integrate SoftwareUCM with CRM platforms, Property Management Systems (PMS), ERP systems, customer service platforms, and similar systems to create seamless business continuity. The available API and SDK also allows for custom functionality and integrations.

SoftwareUCM Pricing Structure

Base Package	Additional 50 Users	Additional 250 Users		
Base package with annual fee	Upgrade package with annual fee	Upgrade package with annual fee		
50 users	Adds 50 users	Adds 250 users		
.	۸	Adds 64 concurrent calls		
24 concurrent calls	Adds 16 concurrent calls	64 concurrent		

Contact Your Grandstream Distributor, Installer, or Representative for Pricing

Supported UC Endpoints and Client Devices	Supports all SIP endpoint access Wave app for desktop (Windows 10+, Mac OS 10+), web (Firefox, Chrome, Safari, Edge, Opera) and mobile (Android & iOS), Wave extension for Google Chrome					
Call Features	Call park, call forward, call transfer, call waiting, caller ID, call record, call history, ringtone, IVR, music on hold, call routes, DID, DOD, DND, DISA, ring group, ring simultaneously, time schedule, PIN groups, call queue, pickup group, paging/intercom, voicemail, call wakeup, SCA, BLF, voicemail to email, fax to email, speed dial, call back, dial by name, emergency call, call follow me, blacklist/whitelist, voice conference, video conference, eventlist, feature codes, busy camp-on/ call completion, voice control, post-meeting reports, virtual fax sending/receiving, email to fax, scheduled call, announcement, announcement center, operator panel, time condition routing					
Customer Relationship Management (CRM)	Supports integration with SugarCRM, Vtiger, Zoho, Salesforce, ACT!, and ODOO					
Calling with WebRTC Trunk	Supports mobile and desktop web browsers: Chrome, Edge , Safari, Firefox , Opera Supports mobile application with built-in WebRTC WebView, including Whatapps, Facebook, Weixin, and more					
Collaboration	Audio and Video Meetings/Conferences, Instant Messaging and Group Chats with End-to-End Encryption, File Sharing, Screen Sharing, In-Meeting Chat, Voice Detection, Meeting Recording, Polls, Surveys, Message status, Advance Whiteboard with Multiplayer Annotation, Meeting Assistant, Onsite Meeting Room Scheduling, and more					
Online Customer Service	Supports integration with third-party customer service platforms, including WhatsApp and Telegram. And built-in live chat					
Call Center	Multiple configurable call queues, automatic call distribution (ACD) based on agent skills/availability/ work-load, in- queue announcement					
Customizable Auto Attendant	Up to 5 layers of IVR (Interactive Voice Response) in multiple languages					
Property Management System (PMS)	Supports Integration with Hmobile, Mitel, HSC, IDS, PMS API, and local PMS					
SoftwareUCM App store	Support more than 20 customized applications, with new apps being added regularly • CRMs add-ons • Google Drive and Office 365 • Whatapps and Telegram • Hotdesking					
Microsoft Integration	Supports Integration with Microsoft Teams (via TeamMate), Outlook, AD Contact, and Office 365					
Computer Telephony Integration (CTI)	CTI Mode to Control GXP, GRP, GXV, and GHP Series IP Phone					
Wired and Bluetooth Headsets	Supports docking with different types of headphones Supported Microsoft Teams certified headsets, supports phone call control					
Maximum Attendees of Conference Bridges						
Firmware Upgrade and Provisioning						
IP Cameras, Intercom and Door Access Integration						
API and SDK	Full CGI API available for third-party platform and application integration Wave add-on SDK Wave Andriod and iOS SDK Wave H5 Embedded for MAC/Windows applications					
Multi-Language Support	 Web UI: English, Simplified Chinese, Traditional Chinese, Spanish, French, Portuguese, German, Russian, Italian, Polish, Czech, Turkish Customizable IVR/voice prompts: English, Chinese, British English, German, Spanish, Greek, French, Italian, Dutch, Polish, Portuguese (Brasileiro), Portuguese (Portugues), Russian, Swedish, Turkish, Hebrew, Arabic, Nederlands, Customizable language pack to support other languages 					
Security	Frequency Restriction, Fail2ban, Ping Defense, Ping Of Death, SYN-Flood, Remote login interception, Multi-factor authentication, SMS login authentication, Static Firewall Defense, Web login IP allow list, Data and File Encryption					
Network Protocols	SIP, TCP/UDP/IP, RTP/RTCP, IAX, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, STUN, SRTP, TLS, LDAP, IPv4, OpenVPN®, SMB2, SNMP, 802.1x, Radius					
Internet Protocol Standards	RFC 3261, RFC 3262, RFC 3263, RFC 3264, RFC 3515, RFC 3311, RFC 4028. RFC 2976, RFC 3842, RFC 3892, RFC 3428, RFC 4733, RFC 4566, RFC 2617, RFC 3856, RFC 3711, RFC 4582, RFC 4583, RFC 5245, RFC 5389, RFC 5766, RFC 6347, RFC 6455, RFC 8860, RFC 4734, RFC 3665, RFC 3323, RFC 3550, RFC6189					
Caller ID	SIP From PAI, RPID, PPI, and head field					
	In-band audio, RFC4733 and SIP INFO					
Transmission Encryption	SRTP, DTLS-SRTP, TLS, HTTPS, 802.1.x, SSH, ZRTP					
Voice-over-Packet Capabilities	Comfort noise, NACK, NACK+RTX Dynamic Jitter Buffer, NetEQ, FEC 2.0, jitter resilience up to 50% audio packet loss					
Voice and Fax Codecs Video Codecs	Opus, G.711 A-law/U-law, G.722, G722.1 G722.1C, G.723.1 5.3K/6.3K, G.726-32, G.729A/B, iLBC, GSM; T.38 H265, H.264, H.263, H263+, VP8					
QoS	Layer 3 (ToS, DiffServ, MPLS) QoS					

Specifications

Maximum Extensions	5000
Maximum Calls	1000
License Activation Method	Online and Offline Activation
	• X86 base hardware server or PC • Supports installation in Hypervisors software

Deployment Mode

SoftwareUCM supports two deployment modes:

- Single Tenant: After installing the SoftwareUCM ISO software, only one SoftwareUCM software instance can be created. In this mode, the resource usage of the entire machine is considered as one specification.
- Multi-Tenant: After installing the SoftwareUCM ISO software, you can choose to create a multi-instance mode. In this mode, each SoftwareUCM instance needs to be configured with independent CPU resources, memory, and disk space. Therefore, the server requirements must include the resources needed for multiple instances.

System Requirements

CPU

- x86-based CPU installs require compatibility with 64-bit architecture and can be used as "Bare Metal" or "Virtual Machine" deployments.
- Using Call Queues and group calls uses more CPU more resources than 1-on-1 calls, depending on the number of the end-points.
- The CPU resources used by each SoftwareUCM Instance are exclusive. In Multi-instance mode, the resources required by the entire machine need to be combined for calculation.

Memory

SoftwareUCM requires at least 2GB of memory. In addition to the specification requirements indicated in the specification list, allocating users in multiple extension groups or queues increases the need for additional RAM - adjust according to the deployment enviornment.

Storage

- Allocate at least 30GB for the SoftwareUCM base system installation
- Add extra space for backup, voicemail, recordings or logging. Keep in mind:
 - Audio Recording and voicemail: 1 minute of recorded audio consumes is approximately 1MB with compression enabled
 - Video Recording: 1 hour of recorded video consumes up to 500MB
 - Logging: Verbose logs on a busy system can consume up to 300MB
- · Offload (archive) unneeded recordings, voicemail, and backups to cold storage regularly to optimize free space available on your PBX

Network

- SoftwareUCM requires at least a 1Gb LAN network connectivity, depending on the number of simultaneous calls and usage of other network applications.
- 10Gb is required for 3000+ extensions

Virtual Machine Software Requirements

- · SoftwareUCM is validated for use with the following Hypervisors:
 - VMware Workstation: 16.1.0 or later
 - Hyper-V: 10.0.19041.1 or later
 - KVM: 4.5.0 or later
 - VirtualBox: 7.0 or later

Server Resource Requirements

Maximum Extensions	1-100	101-200	201-400	401-1000	1001-2000	2001-3000	3001-5000	
Maximum Calls	1-20	21-40	41-80	81-160	161-320	321-450	451-1000	
CPU Recommended	Intel i5 (Gen.8) or equivalent	Intel i7 (Gen.8) or equivalent	Intel Xeon E5 v4 or equivalent				
CPU Threads/vCPUs (Frequency larger than 2.4GHz)	2	3	4	8	12	16	32	
Memory	2GB	3GB	4GB	8GB	12GB	16GB	32GB	
Storage (No Records)	30GB	40GB	60GB	200GB	400GB	500GB	500GB	
	Recommended: 1 TB							

Storage (With Records) -1GB storage space can record 1000 minutes of voice

-1GB storage space can record 2 hours of video

You can configure the appropriate storage space according to your recording needs