

Akin 1000


PN: PWAV-10001AK-AZ01B

EAN: 6422956005436

The worthy protector



Digital display



Time delay function



Selectable input voltage range



★ Features

- ⊕ Microprocessor control guarantees high reliability
- ⊕ Selectable input voltage range
- ⊕ Time delay function eliminates transients that can effect connected equipment
- ⊕ Under-voltage, over-voltage, over-heat and over current protection
- ⊕ Provides stable output voltage
- ⊕ Provide surge and spike suppression

📄 Specifications

Capacity	1000VA / 800W	Full Protection	over-voltage under-voltage over-heat over current protection
Socket type	1x schuko	Indicators	
Input		LED Indicator	normal indicator AVR indicator delay time setting fault indicator
Nominal Voltage	220 VAC	Normal Mode	Green lightning
Voltage Range	110 VAC - 270 VAC or 140 VAC - 260 VAC (Selectable)	Activate voltage range switch Mode	Yellow & Green led lighting
Frequency Range	60 Hz or 50 Hz	Output Adjustable Voltage Range Mode	Red & Green led lighting
Output		Time Delay	Red led Flashing & Green lighting
Nominal Voltage	220 VAC	Digital Display	Input and output voltage
Voltage Regulation	± 10%		
Efficiency			
Normal Mode	95%		
AVR Mode	92%		
Protection			
Delay Time	3 minutes or 10 Seconds		

Physical

Dimension,
D X W X H (mm) 196.8 x 110 x 123.5




Net Weight (kgs) 3.91

Environment

Operating
Temperature 0- 40°C

Humidity 0-90 % relative humidity
(Non-condensing)

Logistics

 Carton Box Size	201 x 302 x 504 mm
 Pieces in the Carton Box	4 pcs / ctn
 Net & Gross weight / CTN	N.W. / G.W.: 17.7 kg / 18.4 kg

Certificates

