

Horus Plus 600

The power keeper

PN: PWUP-LI060H1-AZ01B

EAN: 6422956006419

Specifications

Capacity	600 VA / 360 W
Type	Line Interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	170-280 VAC
Frequency Range	60/50 Hz (auto sensing)
Output	
Nominal Voltage	230 VAC
AC Voltage Regulation (Batt. Mode)	±10%
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz
Waveform (Batt. Mode)	Simulated Sine Wave
Transfer Time	Typical 2-6 ms
AVR	
Type	2 Boost / 1 Buck
Indicators type	
LCD Display	Input voltage, output voltage, battery capacity, load level and UPS status
Alarm	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 seconds
Fault	Continuously sounding
Protection	
Outlets type	2 x Schuko Battery Backup 2 x RJ11 (IN/OUT) for modem/phone surge protection
Full protection	Over/ under voltage protection, Overload, Discharge and Overcharge Protection



Software Included



Auto-Restart



LCD Touchscreen display

- Touchscreen LCD to display UPS information circularly
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- Software Management (ViewPower)

Environment

Humidity 0-90 % RH @ 0-40°C
(non-condensing)

Noise level Less than 40dB

Battery

Battery Type & Number 1x GP07122L
PN: BTVACEUOATG2LAZ01B

Typical Recharge Time 4-6 hours up to 90% capacity

Running time on battery (minutes)
25% Load - 21min
50% Load - 7 min
75% Load - < 2 min
100% Load - < 1 min

Management

Connection port USB

Software <https://www.power-software-download.com/viewpower.html>

Software capability Monitor & Control over USB



Physical

Product dimensions 300 x 101 x 142 mm


Product weight 4.35 kg

Retail Pack Dimensions 344 x 134 x 221 mm

Retail Pack Weight 4.56 kg



Running time on battery



Logistics

Carton Box Size	593 x 355 x 240 mm
Pieces in the Carton Box	4 pcs / ctn
Net & Gross weight / CTN	N.W. / G.W.: 17.6 kg / 19.6 kg



Certificates

RoHS 2011/65/EU

