

Dawn 750

Multiply the power

PN: PSAT5075A40CNC001B

EAN: 6422956009908



Specifications

| | |
|--|---|
| Type | PSU 750W ATX 12V 2.3 |
| Power Factor Correction | Active PFC |
| Input Voltage | 230V |
| Input Frequency | 47 – 63Hz |
| Output Capacity | 750W |
| Modular | No |
| Number of Rails +12V | 1 x 61A |
| Capacitors | High quality 105° C |
| Protection | OVP / OPP / OCP / SCP |
| Thermal Control | Intelligent auto-thermal fan control |
| Efficiency | Meets 80+ Bronze 230V version 85% / 88% / 85% (20% / 50% / 100% load) |
| DC to DC Technology | No |
| NVIDIA SLI | Yes |
| ATI CrossFireX | Yes |
| Power cord | 1 x 150 cm |
| Fan Type | 140 mm |
| Noise level | 24dB |
| Cables | Flat |
| Product Dimensions (L x W x H mm) | 160 x 150 x 86 mm |
| Product Weight | 1.7 kg |
| Retail Pack Dimensions (L x W x H mm) | 270 x 180 x 100 mm |
| Retail Pack Weight | 2.12 kg |




Recommended
for gamers




Active
PFC




105° C
capacitors



1 x 20+4pin




1 x ATX/EPS 12V



4 x PCI-E 6+2pin



6 x SATA




4 x 4pin Molex



Connectors & cable lengths


1 x Motherboard 20+4pin

550 mm




1 x CPU 4+4pin

60mm




2 x PCI-E 6+2pin

550 mm




150 mm




2 x PCI-E 6+2pin

550 mm




150 mm




2 x 4pin Molex and 3 x SATA


500 mm




150 mm




150 mm



150 mm




150 mm




2 x 4pin Molex and 3 x SATA


500 mm




150 mm




150 mm






150 mm



150 mm



Logistics

| | | |
|---|--------------------------|------------------------------|
|  | Carton Box Size | 525 x 375 x 295 mm |
|  | Pieces in the Carton Box | 10 pcs / ctn |
|  | Net & Gross weight / CTN | N.W. / G.W.: 17 kg / 21.2 kg |



Certificates

RoHS
2011/65/EU

