

hAP ac²

The hAP ac² is a Dual-concurrent Access Point, that provides Wifi coverage for 2.4 GHz and 5 GHz frequencies at the same time. Five 10/100/1000 Ethernet ports provide Gigabit connections for your wired devices, and USB can be used for external storage or 4G/LTE modem.

New design universal case allows unit to be positioned either horizontally (desktop) or vertically (tower case). Wall anchored mounting kit is provided.



- Dual chain wireless 2.4 GHz
- Dual chain wireless 5 GHz
- 4 core 716 MHz CPU
- 128 MB of RAM
- Five x 10/100/1000 Mbps Ethernet ports
- USB port for 3G/4G modem



The hAP ac² can be powered from the power jack or with passive PoE from a PoE injector. The power adapter is included.

The hAP ac² is preconfigured, so all you need to do, is plug in the Internet cable, the power, and start using the internet by connecting to the MikroTik network.



Can be attached to the wall.



24 V 0.8 A power adapter



Specifications

Product code	RBD52G-5HacD2HnD-TC (International) RBD52G-5HacD2HnD-TC-US (USA)		
CPU	IPQ-4018 716 MHz		
CPU core count	4		
Size of RAM	128 MB		
Storage type	Flash		
Storage size	16 MB		
10/100/1000 Ethernet ports	5		
Wireless bands	5 GHz radio	2.4 GHz radio	
Wireless regulations	Specific frequency range may be limited by country regulations		
Operating frequency	International	5150 - 5875 MHz	International 2412 - 2484 MHz
	USA	5170 - 5250 MHz 5725 - 5835 MHz	USA 2412 - 2462 MHz
Protocols	802.11a/n/ac		802.11b/g/n
Chains	Dual-chain		Dual-chain
Antenna gain	2.5 dBi		2.5 dBi
Wireless chip model	IPQ-4018		IPQ-4018
Antenna beam width	360°		
PoE in	Yes (18 - 28 V)		
Supported input voltage	12 V - 30 V (Jack or Passive PoE)		
Operating temperature	-40°C .. +70°C		
Extras	USB 2.0 Type A full size port, 1 A		
Dimensions	34 x 119 x 98mm		
License level	4		
Operating System	RouterOS		
Max Power consumption	15 W		

Wireless specifications

RATE (2.4 GHz)	Tx (dBm)	Rx (dBm)	RATE (5 GHz)	Tx (dBm)	Rx (dBm)
1MBit/s	27	-100	6MBit/s	26	-96
11MBit/s	27	-94	54MBit/s	22	-80
6MBit/s	27	-96	MCS0	26	-96
54MBit/s	24	-78	MCS7	21	-75
MCS0	27	-96	MCS9	19	-70
MCS7	23	-73			